MODEL 180058




Cable Matters® 12-Port Cat 6 Vertical Mini Patch Panel with 89D Bracket and mounting screws

INSTALLATION INSTRUCTIONS

3


4




Remove the 89D Bracket




• Strip about 1.5 inches of the cable jacket, trim the spine, and separate the pairs




568B Wiring Shown






- UNSHIELDED 10 INCH VERTICAL PATCH PANEL
- 110 OR KRONE COMPATIBLE IDC TERMINALS
- SUPPORTS 568A AND 568B WIRING
- CATEGORY 6 TIA/EIA 568-C.2 PERFORMANCE
- SUPPORTS 22-26 AWG SOLID OR STRANDED WIRE



- Untwist each wire pair about 1/2"
- · Keep the twists as tight as possible
- Insert the cable pairs into the IDC terminals
- Terminate the cable with either a Krone or 110 impact tool
- Orient the tool with the **CUT** side on the outside

GOVERNMENT USE		COMMERCIAL/RESIDENTAL US	
T568A		T568B	
Pin 5	White/Blue	Pin 5	White/Blue
Pin 4	Blue	Pin 4	Blue
Pin 1	White/Green	Pin 1	White/Orange
Pin 2	Green	Pin 2	Orange
Pin 3	White/Orange	Pin 3	White/Green
Pin 6	Orange	Pin 6	Green
Pin 7	White/Brown	Pin 7	White/Brown
Pin 8	Brown	Pin 8	Brown



- Dress the cables pair to feed through the top and bottom and secure with wire ties for the best cable management
- Install the 89D bracket vertically on the wall with the included screws
- Snap the patch panel into the 89D bracket

EMAIL: SUPPORT@CABLEMATTERS.COM

